

Fuse / 57002

**PU/Rubber Sole**

Manufactured with a high durability PU/ Rubber for more comfort and protection in heavy industrial environments.

|               |                      |                             |  |
|---------------|----------------------|-----------------------------|--|
| <b>Female</b> | <b>Size</b><br>3 - 9 | <b>Colour</b><br>Black/Grey | <b>Accreditation</b><br>SANS/ISO 20345 |
|---------------|----------------------|-----------------------------|--|



Electrical resistance to 20 KVA for 60 seconds (Eskom spec 34-232)

**STANDARD FIT**

- Upper:**
  - Cut from 1.8 - 2.0mm Full Grain Leather
  - 20mm padded collar from mesh fabric for enhanced comfort, breathability and support
  - 2 pairs rust resistant eyelet lace-up
  - 4 pairs rust resistant d ring lace-up
  - Braided lace from polyester yarn and central core for additional strength
- Lining:**
  - The vamp lining is from a hi-tech needle-fibre blend with excellent perspiration absorbency and is treated with *Ultra-Fresh\** to impart hygienic and anti-bacterial properties to the material
- In-Sock:**
  - The in-sock is from an anti-static non-woven material
  - The top sock features Footology PU footbed with microfibre
- Sole:**
  - The rubber outsole is heat, cut and abrasion resistant and provides SRC rate resistance on most surfaces
  - The cushioned midsole is made from a flexible low density Polyurethane with a shore hardness of 45-55
  - The outer sole is made from a high density PU/Rubber with a shore hardness of 60-75
- Toe Cap:**
  - Steel toe cap
  - Can withstand an impact load of 200 joules

The SiSi Fuse boot has been tested to comply with the SANS/ISO 20345 safety footwear specifications and carries this stamp of approval.