

Yvonne / 55013

Dual Density Polyurethane Sole

Manufactured with direct injection-moulded dual density polyurethane for more comfort and protection in heavy industrial environments.

Sex	Sizes	Colour	Accreditations
Female	3-8	Black with grey stitching	EN/ISO 20345



Standard Fit

Upper:

- Cut from 2.0mm - 2.2mm Barton Print Water Buffalo Hides
- Padded collar from a PVC stretch back material with a soft latex rubber padding for enhanced comfort and support
- Padded tongue from a soft PVC coated fabric for improved comfort
- 4 pair D-Ring lace-up with corrosion-resistant gunmetal coating
- Braided lace from polyester yarn and central core for additional strength

Lining:

- The quarter lining is from an industrial ferrabelle non-woven material
- The vamp lining is from a hi-tech needle-fibre blend with excellent perspiration absorbency and is treated with **Ultra-Fresh*** to impart hygienic and anti-bacterial properties to the material

In-Sock:

- The in-sock is from an anti-static non-woven material

Sole:

- The sole is from a dual density PU/PU
- The midsole is from a low density flexible Polyurethane with a shore hardness of 0.45mm - 0.50mm
- The outer sole is from Polyurethane with a shore hardness of 0.64mm - 0.65mm
- A shank reinforcement is moulded into the midsole for additional arch support
- This shoe can withstand temperatures of up to 95°C
- This shoe is anti-static

Toe Cap:

- Steel toe cap
- Can withstand an impact load of 200 joules

The Yvonne shoe has been tested to comply with EN/ISO 20345 specifications and carries the EN/ISO 20345 certified mark.

This product is manufactured in South Africa by BBF Safety Group (Pty) Ltd. in an ISO 9001:2000 accredited factory.

FEBRUARY 2020