

Opal / 53003

Single Density Polyurethane Sole

Manufactured with direct injection-moulded single density polyurethane, this range is suited to light industrial environments.

Sex	Sizes	Colour	Accreditations
Female	2 - 9	Black / Brown	SANS/ISO 20345



Narrow Fit

Upper:

- Cut from 2.0 - 2.2mm smooth Full Grain Leather
- 10mm padded tongue with half bellows for enhanced comfort to the wearer
- 7 pair rust resistant D-ring lace-up for quick removal of boot
- Braided lace from polyester yarn and central core for additional strength

Lining:

- The quarter lining is from an industrial ferrabelle non-woven material
- The vamp lining is from a hi-tech needle-fibre blend with excellent perspiration absorbency and is treated with **Ultra-Fresh*** to impart hygienic and anti-bacterial properties to the material

In-Sock & Top Sock:

- The in-sock is from an anti-static non-woven material
- The Energiser top sock is from a combination of polyester and wool, with excellent perspiration absorbency
- The top sock features EVA foam inserts on the ball and heel area for enhanced comfort and shock absorption
- The top sock has been treated with **Ultra-Fresh*** to impart hygienic and anti-bacterial properties to the material

Sole:

- The sole is from a single density Polyurethane with a shore hardness of 0.64mm - 0.65mm
- A shank reinforcement is moulded into the midsole for additional arch support
- This boot can withstand temperatures of up to 95°C
- This boot is anti-static

Toe Cap:

- Steel toe cap
- Can withstand an impact load of 200 joules

The Opal boot has been tested to comply with SANS/ISO 20345 specifications and carries the SANS/ISO 20345 certified mark

This product is manufactured in South Africa by BBF Safety Group (Pty) Ltd. in an ISO 9001:2000 accredited factory.

JULY 2018